







## Method for manufacturing ceramic-based composite material

Publication number: EP1063210  
Publication date: 2000-12-27  
Inventor: YOSHIDA TAKASHI (JP); NISHIDE SHIGETO (JP)  
Applicant: ISHIKAWAJIMA HARIMA HEAVY IND (JP)  
Classification:  
- International: C04B35/571; C04B35/80; C04B35/565; C04B35/80;  
(IPC1-7); C04B35/571; C04B35/80  
- European: C04B35/571; C04B35/80D  
Application number: EP20000106153 20000321  
Priority number(s): JP19990179367 19990625

### Also published as:

 US6342269 (B1)  
 JP2001010863 (A)  
 CA2299603 (A1)  
 EP1063210 (B1)

### Cited documents:

 WO9731064  
 EP0781737


Report a data error here

### Abstract of EP1063210

A matrix formation process 10 is configured with CVI process 12 and PIP process 14, 15, 16 in which a co-polymer containing at least polycarboxysilane (PCS) and polymethylsilane (PMS) is applied. Crosslinking of each polymer is performed at an intermediate temperature which is lower than the pyrolysis temperature of the polymeres. Polymer impregnation process 15 for infiltrating the co-polymer into a matrix, and inert gas firing process 16 for firing the material at a high temperature in an inert gas atmosphere. In the crosslink process, the mixed polymer is held at about 573K to 723K for a predetermined time. The conversion ratio of the co-polymer crosslinked into SiC in the subsequent firing process is increased, efficiency of filling SiC in the PIP process is increased, and an airtight ceramic-based composite material can be manufactured efficiently within a short time.

BEST AVAILABLE COPY

Fig. 1



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY